

EcooSetter UV-400A Automatic CTP



Model: EcooSetter UV-400A F/S/E Laser wavelength: 400-410nm

Plate: UV plate, high-sensitive PS plate

| Model | T-400 FA | T-400 SA | T-400 EA | UV-400 FA | UV-400 SA | UV-400 EA |
|--------------------------|---|----------|----------|-----------|-----------|-----------|
| Imaging System (channel) | 48 | 32 | 24 | 48 | 32 | 24 |
| Throughput (plates/hour) | 28 | 22 | 16 | 28 | 22 | 16 |
| | 800mm× 660mm 2400dpi | | | | | |
| Plate Size | Max.800mm × 660mm, Min.400mm × 300mm | | | | | |
| Plate Thickness | 0.15mm to 0.30mm | | | | | |
| Resolutions | 2400dpi | | | | | |
| Repeatablity | $\pm 5\mu m$ (Continuous exposing for four times or above on the same plate with a temperature of 23 $^\circ\!$ | | | | | |
| Weight | 1000 KG | | | | | |
| Size (WxDxH) | 1600mm × 1410mm × 1120mm (W × D× H) | | | | | |
| Power Supply | Single-phase: 220AC, +6%, -10%, Power Consumption: 4KW | | | | | |
| Environment | Recommended: 21-25 ℃ , Max.18-26 ℃ , humidity: 40-70% | | | | | |