

CTCP Long Run Plate(Single Layer)

ECOO-CTCP



EcooGraphix

| | |
|----------------------------------|---|
| Model | ECOO-CTCP |
| Plate Type | Positive CTCP Plate |
| Application | High grade commercial and newspaper printing |
| Substrate | Electro chemically Grained and Anodized lithographic Aluminum |
| Gauge | 0.15, 0.20, 0.25, 0.30, 0.40(mm) |
| Maximum short grain width | Maximum width 1280 mm |
| Coating | IR sensitive, positive acting |
| Length of Run | 100,000 impressions |
| Plate setters | Luscher, Baysprint, Cron, EcooGraphix |
| Aluminum | Standard 1050 Alloy |
| Exposure energy | 40 – 50 mj/ cm ² |
| Developing time | 25-30 sec |
| Spectral Sensitivity | 400 – 410 nm |
| Resolution | 1-99% @ 200LPI |
| Image Color | Green |
| Processing Speed | 0.80 – 1.20 m/min |
| Developer | All kind brands developer or our own developer |
| Processing temperature | 23 °C +/-2 °C |
| safelight | Handle under yellow safelight(UV free) |
| Shelf life | 12 months under recommended storage conditions |
| Packaging | Available in all standard formats, including bulk packaging options such as APL packaging |
| Storage and handing | Stored in a cool and dry environment, away from excessive cold, heat and humidity |



Hangzhou EcooGraphix Digital Technology Co, Ltd.

Add: Room 708, Tianheng Building, No.1509, Binsheng Rd, Binjiang District, Hangzhou, China

Tel: 0086 571-87391001 Fax:0086 0571-87391001

E-mail:info@ecoographix.com Website: www.ecoographix.com