

CTCP Long Run Plate(Single Layer) ECOO-CTCP



EcooGraphix

Model	ECOO-V
Plate Type	Positive CTCP Plate
Application	High grade commercial and newspaper printing
Substrate	Electro chemically Grained and Anodized lithographic Aluminum
Gauge	0.15, 0.20, 0.25, 0.30, 0.40(mm)
Maximum short grain width	Maximum width 1280 mm
Coating	IR sensitive, positive acting
Length of Run	100,000 impressions
Plate setters	Luscher, Baysprint, Cron, EcooGraphix
Aluminum	Standard 1050 Alloy
Exposure energy	40 – 50 mj/ m ²
Developing time	25-30 sec
Spectral Sensitivity	400 – 410 nm
Resolution	1-99% @ 200LPI
Image Color	Green
Processing Speed	0.80 – 1.20 m/min
Developer	All kind brands developer or our own developer
Processing temperature	23°C +/-2°C
safelight	Handle under yellow safelight(UV free)
Shelf life	12 months under recommended storage conditions
Packaging	Available in all standard formats, including bulk packaging options such as APL packaging
Storage and handing	Stored in a cool and dry environment, away from excessive cold, heat and humidity



Hangzhou EcoGraphix Digital Technology Co, Ltd.

Add: Room 708, Tianheng Building, No.1509, Binsheng Rd, Binjiang District, Hangzhou, China

Tel: 0086 571-87391001 Fax:0086 0571-87391001

E-mail:info@ecoographix.com Website: www.ecoographix.com